

LINCE VERSO 2M

LINCE VERSO 2M INDOOR

INSTRUCCIONES DE MONTAJE

MOUNTING INSTRUCTIONS

MONTAGEANLEITUNG




INSTRUCTIONS DE MONTAGE










LCEVERSO2M	LCV.2M.08000	A453 B160 H229	50W	56W	7.7Kg	0.18-0.28	Tc 85°C
LCEVERSO2M	LCV.2M.10000	A453 B160 H229	65W	74W	7.7Kg	0.24-0.37	Tc 85°C
LCEVERSO2M	LCV.2M.13000	A453 B160 H229	90W	99W	7.7Kg	0.32-0.50	Tc 85°C
LVIVERSO2M	LVI.2M.08000	A453 B160 H229	50W	56W	7.7Kg	0.18-0.28	Tc 85°C
LVIVERSO2M	LVI.2M.10000	A453 B160 H229	65W	74W	7.7Kg	0.24-0.37	Tc 85°C
LVIVERSO2M	LVI.2M.13000	A453 B160 H229	90W	99W	7.7Kg	0.32-0.50	Tc 85°C

LEC
Light Environment Control

Polígono Industrial El Olivar, Calle Copejadores Nº2 · 11160 Barbate (Cádiz) España-Spain
Tel.: +34 956 454 130 ·
info@lecsl.com | www.lecsl.com



“Empresa certificada en diseño y fabricación de luminarias LED”

 IP-65	 Ref.		 f		 Tw	 Tc
DRIVER (LCV.2M.08000)	LECLAY0070CFNT000	198-305 V	50/60 Hz	0.18-0.28A	Tw 80°C	Tc 85°C
DRIVER (LCV.2M.10000)	LECLAY0090CFNT001	198-305 V	50/60 Hz	0.24-0.37A	Tw 80°C	Tc 85°C
DRIVER (LCV.2M.13000)	LECLAY0110CFNT001	198-305 V	50/60 Hz	0.32-0.50A	Tw 80°C	Tc 85°C
DRIVER (LVI.2M.08000)	LECLAY0070CFNT002	198-305 V	50/60 Hz	0.18-0.28A	Tw 80°C	Tc 85°C
DRIVER (LVI.2M.10000)	LECLAY0090CFNT000	198-305 V	50/60 Hz	0.24-0.37A	Tw 80°C	Tc 85°C
DRIVER (LVI.2M.13000)	LECLAY0110CFNT000	198-305 V	50/60 Hz	0.32-0.50A	Tw 80°C	Tc 85°C



ES Realizar periódicamente una limpieza de los componentes no electrónicos con un paño.

EN Clean the non-electronic components regularly with a cloth.

DE Reinigen Sie die nichtelektronischen Komponenten regelmäßig mit einem Tuch.

FR Réaliser de manière périodique le nettoyage des composants non électroniques avec un chiffon.

