

LINCE EFFICACY 1M / 2M

LINCE EFFICACY 1M / 2M INDOOR

INSTRUCCIONES DE MONTAJE

MOUNTING INSTRUCTIONS

MONTAGEANLEITUNG

INSTRUCTIONS DE MONTAGE



Serie	Material	LED SMD	Light Output	Weight	Beam Spread	Tc
L EFFICACY 1M LCF/LEL1M.03500	A249 B155 H224	16,5W	19W	4,5Kg	0.06-0.10	Tc 85°C
L EFFICACY 1M LCF/LEL1M.04000	A249 B155 H224	21W	24W	4,5Kg	0.08-0.12	Tc 85°C
L EFFICACY 1M LCF/LEL1M.06000	A249 B155 H224	32W	38W	4,5Kg	0.12-0.19	Tc 85°C
L EFFICACY 1M LCF/LEL1M.08000	A249 B155 H224	49W	54W	4,5Kg	0.18-0.27	Tc 85°C
L EFFICACY 2M LCF/LEL2M.09000	A453 B160 H229	48W	54W	7.7Kg	0.18-0.27	Tc 85°C
L EFFICACY 2M LCF/LEL2M.12000	A453 B160 H229	76W	81W	7.7Kg	0.27-0.41	Tc 85°C
L EFFICACY 2M LCF/LEL2M.15000	A453 B160 H229	103W	112W	7.7Kg	0.35-0.54	Tc 85°C



Polígono Industrial El Olivar, parcela M-15 · 11160 Barbate (Cádiz) España-Spain







Tel.: +34 956 454 130 ·

info@lecsl.com | www.lecsl.com



AC 198-305 V
50/60 Hz

“Empresa certificada en diseño y fabricación de luminarias LED”

 IP-65	Ref.					
DRIVER (LCF/LEI.1M.03500)	LECLAY0040CFNT003	198-305 V	50/60 Hz	0.06-0.10A	Tw 80°C	Tc 85°C
DRIVER (LCF/LEI.1M.04000)	LECLAY0040CFNT003	198-305 V	50/60 Hz	0.08-0.12A	Tw 80°C	Tc 85°C
DRIVER (LCF/LEI.1M.06000)	LECLAY0040CFNT003	198-305 V	50/60 Hz	0.12-0.19A	Tw 80°C	Tc 85°C
DRIVER (LCF/LEI.1M.08000)	LECLAY0070CFNT002	198-305 V	50/60 Hz	0.18-0.27A	Tw 80°C	Tc 85°C
DRIVER (LCF/LEI.2M.09000)	LECLAY0070CFNT002	198-305 V	50/60 Hz	0.18-0.27A	Tw 80°C	Tc 85°C
DRIVER (LCF/LEI.2M.12000)	LECLAY0090CFNT000	198-305 V	50/60 Hz	0.27-0.41A	Tw 80°C	Tc 85°C
DRIVER (LCF/LEI.2M.15000)	LECLAY0100CFNT000	198-305 V	50/60 Hz	0.35-0.54A	Tw 80°C	Tc 85°C



ES Realizar periódicamente una limpieza de los componentes

DE Reinigen Sie die nichtelektronischen Komponenten

EN Clean the non-electronic components regularly with a cloth.

FR Réaliser de manière périodique le nettoyage des composants non électroniques avec un chiffon.

